This page is not part of the report and is for your information only. This page has not to be sent to the Belgian CAA.

Record of versions

Version number	Date of revision	Topics
1.0	02/12/2015	Initial version

When to use this report?

In case of reporting a skill test for a private pilot licence for helicopters.

Content of the report

- 1. The helicopter used for the skill test shall meet the requirements for training helicopters.
- 2. The area and route to be flown should be chosen by the FE and all low level and hover work should be at an adequate aerodrome or site. Routes used for section 3 may end at the aerodrome of departure or at another aerodrome. The applicant should be responsible for the flight planning and should ensure that all equipment and documentation for the execution of the flight are on board. The navigation section of the test, as set out in this AMC should consist of at least three legs, each leg of a minimum duration of 10 minutes. The skill test may be conducted in two flights.
- 3. An applicant should indicate to the FE the checks and duties carried out, including the identification of radio facilities. Checks should be completed in accordance with the authorised checklist or pilot operating handbook for the helicopter on which the test is being taken. During pre-flight preparation for the test the applicant is required to determine power settings and speeds. Performance data for take-off, approach and landing should be calculated by the applicant in compliance with the operations manual or flight manual for the helicopter used.
- 4. The applicant shall demonstrate the ability to:
 - (a) operate the helicopter within its limitations;
 - (b) complete all manoeuvres with smoothness and accuracy;
 - (c) exercise good judgement and airmanship;
 - (d) apply aeronautical knowledge; and
 - (e) maintain control of the helicopter at all times in such a manner that the successful outcome of a procedure or manoeuvre is never seriously in doubt.

Flight test tolerances

5. The following limits shall apply, corrected to make allowance for turbulent conditions and the handling qualities and performance of the helicopter used.

П	eı	g	ľ	π

normal forward flight \pm 150 feet with simulated major emergency \pm 150 feet hovering IGE flight \pm 2 feet

Tracking on radio aids ± 10°

Heading

normal flight $\pm 10^{\circ}$ simulated major emergency $\pm 15^{\circ}$

Speed

take-off and approach multi-engine -10/+15 knots all other flight regimes ± 15 knots

Ground drift

T.O. hover I.G.E \pm 3 feet

Landing no sideways or backwards movement

se of the helicopter checklists, airmanship, control of the helicopter by external visual reference, anti-icing procedures and principles of nreat and error management apply in all sections.			
	SECTION 1. PRE-FLIGHT/POST-FLIGHT CHECKS AND PROCEDURES	Examiner's initials when test/check completed	
а	Helicopter knowledge, (e.g. technical log, fuel, mass and balance, performance), flight Planning, documentation, NOTAMS, weather briefing		
b	Pre-flight inspection/action, location of parts and purpose		
С	Cockpit inspection, starting procedure		

APPLICANT'S NAME:

	PRE-FLIGHT/POST-FLIGHT CHECKS AND PROCEDURES	initials when test/check completed
а	Helicopter knowledge, (e.g. technical log, fuel, mass and balance, performance), flight Planning, documentation, NOTAMS, weather briefing	
b	Pre-flight inspection/action, location of parts and purpose	
С	Cockpit inspection, starting procedure	
d	Communication and navigation equipment checks, selecting and setting frequencies	
е	Pre-take-off procedure, R/T procedure, ATC liaison-compliance	
f	Parking, Shutdown and Post-flight procedure	
	SECTION 1. Passed	Failed

НС	SECTION 2. OVER MANOEUVRES, ADVANCED HANDLING AND CONFINED AREAS	Examiner's initials when test/check completed
а	Take-off and landing, (lift off and touch down)	
b	Taxi, hover taxi	
С	Stationary hover with head/cross/tail wind	
d	Stationary hover turns, 360° left and right (spot turns)	
е	Forward, sideways and backwards hover manoeuvring	
f	Simulated engine failure from the hover	
g	Quick stops into and downwind	
h	Sloping ground/unprepared sites landings and take-offs	
i	Take-offs (various profiles)	
j	Crosswind, downwind take-off (if practicable)	
k	Take-off at maximum take-off mass (actual or simulated)	
- 1	Approaches (various profiles)	
m	Limited power take-off and landing	
n	Autorotations (FE to select two items from - Basic, range, low speed, and 360° turns)	
0	Autorotative landing	
р	Practice forced landing with power recovery	
q	Power checks, reconnaissance technique, approach and departure technique	
	SECTION 2. Passed [☐ Failed ☐

	of the helicopter checklists, airmanship, control of the helicopter by external visual reference, anti-icing procedure it and error management apply in all sections.	s and principles of
	SECTION 3. NAVIGATION - EN-ROUTE PROCEDURES	Examiner's initials when test/check completed
а	Navigation and orientation at various altitudes/heights, map reading	
b	Altitude/height, speed, heading control, observation of airspace, altimeter setting	
С	Monitoring of flight progress, flight log, fuel usage, endurance, ETA, assessment of track error and re-establishment of correct track, instrument monitoring	
d	Observation of weather conditions, diversion planning	
е	Use of navigation aids (where available)	
f	ATC liaison and observance of regulations, etc.	
	SECTION 3. Passed [Failed
F	SECTION 4. FLIGHT PROCEDURES AND MANOEUVRES BY SOLE REFERENCE TO INSTRUMENTS	Examiner's initials when test/check completed
а	Level flight, control of heading, altitude/height and speed	
b	Climbing and descending turns to specified headings	
	Level turns with up to 300hank 1800 to 3600 left and right	

APPLICANT'S NAME:

Level turns 180º left and right by sole reference to instruments

SECTION 4. Passed
Failed

APPLICANT'S NAME:	

Use of the helicopter checklists, airmanship, control of the helicopter by external visual reference, anti-icing procedures and principles of threat and error management apply in all sections.

	SECTION 5. ABNORMAL AND EMERGENCY PROCEDURES	Examiner's initials when test/check completed		
	Note (1) Where the test is conducted on a multi-engine helicopter a simulated engine failure drill, including a sapproach and landing shall be included in the test.			
Note	(2) The FE shall select 4 items from the following:			
а	Engine malfunctions, including governor failure, carburetor/engine icing, oil system, as appropriate			
b	Fuel system malfunction			
С	Electrical system malfunction			
d	Hydraulic system malfunction, including approach and landing without hydraulics, as applicable			
е	Main rotor and/or anti-torque system malfunction (flight simulator or discussion only)			
f	Fire drills, including smoke control and removal, as applicable			
	Other abnormal and Emergency procedures as outlined in appropriate flight manual and with reference to Appendix 3 to JAR-FCL 2.240, sections 7 and 8, including for multi-engine helicopters:			
	- Simulated engine failure at take-off:			
	- rejected take-off at or before TDP or safe forced landing at or before DPATO			
g	- shortly after TDP or DPATO			
	- Landing with simulated engine failure:			
	- landing or go-around following engine failure before LDP or DPBL			
	- following engine failure after LDP or safe forced landing after DPBL			
	SECTION 5. Passed 🗌 Failed 🗌			

